

RubyWebDialogs - Examples

Table of Contents

RubyWebDialogs.....	1
Examples.....	1
1. Array.rwd_method.....	2
2. Array.rwd_options.....	3
3. Array.rwd_row.....	4
4. Array.rwd_headers.....	5
5. Array.rwd_form.....	6
6. Hash.rwd_table.....	7

RubyWebDialogs

Examples

Fri Oct 06 19:42:44 UTC 2006

Erik Veenstra <rubywebdialogs@erikveen.dds.nl>

1. Array.rwd_method

```
["aaa", "bbb"].rwd_method("method")
```

... results in:

```
<p align='left'><a action='method/aaa'>Aaa</a></p>  
<p align='left'><a action='method/bbb'>Bbb</a></p>
```

2. Array.rwd_options

```
["aaa", "bbb"].rwd_options
```

... results in:

```
<option>aaa</option>  
<option>bbb</option>
```

3. Array.rwd_row

```
["aaa", "bbb"].rwd_row
```

... results in:

```
<row valign='top'>  
  <p align='left'>aaa</p>  
  <p align='left'>bbb</p>  
</row>
```

4. Array.rwd_headers

```
["aaa", "bbb"].rwd_headers
```

... results in:

```
<row>  
  <p align='left'><b>aaa</b></p>  
  <p align='left'><b>bbb</b></p>  
</row>
```

5. Array.rwd_form

```
["aaa", "bbb"].rwd_form("prefix_", ["1", "2"])
```

... results in:

```
<table>
  <row>
    <p align='right'>aaa:</p>
    <text name='prefix_aaa' value='1' />
  </row>
  <row>
    <p align='right'>bbb:</p>
    <text name='prefix_bbb' value='2' />
  </row>
</table>
```

6. Hash.rwd_table

```
{"aaa"=>"1", "bbb"=>"2"}.rwd_table
```

... results in:

```
<table>
  <row valign='top'>
    <p align='left'>1</p>
  </row>
  <row valign='top'>
    <p align='left'>2</p>
  </row>
</table>
```

.. and ...

```
{"aaa"=>"1", "bbb"=>"2"}.rwd_table("aaa")
```

... results in:

```
<table>
  <row valign='top'>
    <radio name='aaa' value='aaa' />
    <p align='left'>1</p>
  </row>
  <row valign='top'>
    <radio name='aaa' value='bbb' />
    <p align='left'>2</p>
  </row>
</table>
```